

## 特殊合金鋼管 神鋼特殊鋼管(株)製

### KTA-NCI(柿卜) (80Ni-20Cr)

外径	肉厚	定尺長さ
22	3	L
27	3	L

切断不可

### A268 TP-446(23Cr-)

外径	肉厚	定尺長さ
21.3	2.65	L
26.9	2.65	L

切断不可

### KTA-NCI(80Ni-20Cr)

ニッケル、クローム系電熱用材料として特に高温に優れています。  
用途としては、各種電熱材、加熱装置用部品材に適しております。

### TP-446(23Cr)

クローム系電熱用材料として耐熱保護管に適しております。

# 特殊合金鋼管

## NCF600(インコネル)

外径 (O.D)	× 厚さ (W.T)	× 長さ (L)	仕上 (F)
1.59	× 0.5	× 2,000	
3	× 0.5	× 2,000	
3.18	× 0.5	× 2,000	
	0.7	× 2,000	
	0.889	× 2,000	
4	× 1.0	× 2,000	
6	× 1.0	× 2,000	
	1.0	× 4,000	
6.35	× 1.0	× 2,000	
	1.0	× 4,000	
	1.24	× 2,000	
	1.24	× 4,000	
8	× 1.0	× 2,000	
	1.0	× 4,000	
9.53	× 1.0	× 2,000	
	1.0	× 4,000	
	1.24	× 2,000	
	1.24	× 4,000	
10	× 1.0	× 2,000	
	1.0	× 4,000	
12.7	× 1.0	× 2,000	
	1.24	× 2,000	
	1.24	4,000	
13	× 1.0	× 4,000	
14	× 1.0	× 4,000	
19.05	× 1.65	× 2,000	
	1.65	× 4,000	
22.2	× 2.11	× 2,000	
25.4	× 2.3	× 2,000	

## NCF625(インコネル) 単位: mm

外径 (O.D)	× 厚さ (W.T)	× 長さ (L)	仕上 (F)
6.35	× 1.65	× 2,000	
	1.65	× 4,000	
	2.0	× 2,000	
	2.0	× 4,000	
9	× 2.0	× 2,000	
	2.0	× 4,000	

# 特殊合金鋼管

## ハステロイ C-276

外径 (O.D)	× 厚さ (W.T)	× 長さ (L)	仕上 (F)
3.18	× 0.5	× 2,000	
	0.7	× 2,000	
6	× 1.0	× 2,000	
	1.0	× 4,000	
6.35	× 0.889	× 2,000	
	0.889	× 4,000	
	1.0	× 2,000	
	1.0	× 4,000	
	1.65	× 2,000	
	1.65	× 4,000	
	2.11	× 2,000	
	2.11	× 4,000	
8	× 1.0	× 2,000	
	1.0	× 4,000	
	2.0	× 2,000	
	2.0	× 4,000	
9.53	× 1.0	× 2,000	
	1.0	× 4,000	
	1.65	× 2,000	
	1.65	× 4,000	
10	× 1.0	× 2,000	
	1.0	× 4,000	
12.7	× 1.24	× 2,000	
	1.24	× 4,000	
	2.11	× 2,000	
	2.11	× 4,000	
25.4	× 2.0	× 2,000	
	2.0	× 4,000	

## ハステロイ C-22

単位：mm

外径 (O.D)	× 厚さ (W.T)	× 長さ (L)	仕上 (F)
3.18	× 0.5	× 2,000	
	0.72	× 2,000	
6.35	× 0.9	× 2,000	
	0.9	× 4,000	
	1.0	× 2,000	
	1.0	× 4,000	
9.53	× 0.9	× 2,000	
	0.9	× 4,000	
	1.0	× 2,000	
	1.0	× 4,000	
12.7	× 1.24	× 2,000	
	1.24	× 4,000	

# 特殊合金鋼管

## ニッケル 201

単位：mm

外径 (O.D)	× 厚さ (W.T)	× 長さ (L)	仕上 (F)
3	× 0.5	× 2,000	
	0.5	× 4,000	
3.18	× 0.5	× 2,000	
	0.7	× 2,000	
	0.7	× 4,000	
4	× 0.5	× 2,000	
6	× 1.0	× 2,000	
	1.0	× 4,000	
6.35	1.0	× 2,000	
	1.0	× 4,000	
8	× 1.0	× 2,000	
	1.0	× 4,000	
9.53	× 1.0	× 2,000	
	1.0	× 4,000	
	1.24	× 2,000	
	1.24	× 4,000	
10	× 1.0	× 2,000	
	1.0	× 4,000	
	1.2	× 2,000	
	1.2	× 4,000	
12	× 1.0	× 2,000	
	1.0	× 4,000	
	1.2	× 2,000	
	1.2	× 4,000	
12.7	× 1.24	× 2,000	
	1.24	× 4,000	
19.05	× 1.65	× 2,000	
	1.65	× 4,000	
27.2	× 3.0	× 2,000	
	3.0	× 4,000	
34	× 2.8	× 2,000	
	2.8	× 4,000	

外径 (O.D)	× 厚さ (W.T)	× 長さ (L)	仕上 (F)