

薄肉ステンレス溶接管

サイズ		鋼種				
外径 × 肉厚	長さ	sus304	sus316L	sus321	NCF800 (インコロイ)	NAR-AH1
9 × 1.0	4,000	●				
9.5 × 0.6 × 0.8	4,000			●		
	4,000		●			
10 × 0.8 × 1.0	4,000	●	●			
	4,000	●				
11 × 0.8 × 1.0	4,000	●	●			
	4,000	●				
11.5 × 0.75 × 0.8	4,000				●	
	4,000		●			
12 × 0.8 × 1.0	4,000	●	●			
	4,000		●			
12.7 × 0.75 × 1.0	4,000				●	
	4,000	●				
13 × 1.0	4,000	●				
13.5 × 0.8	4,000	●	●			
14 × 0.75 × 0.8 × 1.0	4,000				●	
	4,000	●	●	●		
	4,000	●	●			
15 × 1.0	4,000	●				
16 × 0.75 × 0.8 × 1.0	4,000				●	
	4,000	●				
	4,000	●	●			
17.3 × 1.0	4,000	●				
18 × 1.0	4,000	●				※●
19 × 1.0	4,000	●				

◇光輝焼鈍（BA）仕上げ

◇シーズヒーター用保護管には最適です

◇製造仕様についての詳細はお問い合わせください

◇上記寸法以外についてもご相談に応じます

※長さが6Mの為地方出荷する際、発送の都合上切断となります。